



P0400.BR

Material

Brass.

Technical Notes

To DIN 464. All knurled screws are one piece manufactured. Unlike the official standards sheet they all have a thread up to the head, as shown, but no recess at the thread end.

Order No.	d ₁	l ₁	d ₂	d ₃	h ₁	h ₂	l ₂
P0400.030-004-BR	M 3	4	12	6	7,5	2,5	2
P0400.030-006-BR	M 3	6	12	6	7,5	2,5	2
P0400.030-008-BR	M 3	8	12	6	7,5	2,5	2
P0400.030-010-BR	M 3	10	12	6	7,5	2,5	2
P0400.030-012-BR	M 3	12	12	6	7,5	2,5	2
P0400.030-016-BR	M 3	16	12	6	7,5	2,5	2
P0400.040-006-BR	M 4	6	16	8	9,5	3,5	2
P0400.040-008-BR	M 4	8	16	8	9,5	3,5	2
P0400.040-010-BR	M 4	10	16	8	9,5	3,5	2
P0400.040-012-BR	M 4	12	16	8	9,5	3,5	2
P0400.040-016-BR	M 4	16	16	8	9,5	3,5	2
P0400.040-020-BR	M 4	20	16	8	9,5	3,5	2
P0400.050-006-BR	M 5	6	20	10	11,5	4,0	2
P0400.050-008-BR	M 5	8	20	10	11,5	4,0	2
P0400.050-010-BR	M 5	10	20	10	11,5	4,0	2
P0400.050-012-BR	M 5	12	20	10	11,5	4,0	2
P0400.050-016-BR	M 5	16	20	10	11,5	4,0	2
P0400.050-020-BR	M 5	20	20	10	11,5	4,0	2

Order No.	d ₁	l ₁	d ₂	d ₃	h ₁	h ₂	l ₂
P0400.050-025-BR	M 5	25	20	10	11,5	4,0	2
P0400.050-030-BR	M 5	30	20	10	11,5	4,0	2
P0400.060-008-BR	M 6	10	24	12	15,0	5,0	2
P0400.060-010-BR	M 6	10	24	12	15,0	5,0	2
P0400.060-012-BR	M 6	12	24	12	15,0	5,0	2
P0400.060-016-BR	M 6	16	24	12	15,0	5,0	2
P0400.060-020-BR	M 6	20	24	12	15,0	5,0	2
P0400.060-025-BR	M 6	25	24	12	15,0	5,0	2
P0400.060-030-BR	M 6	30	24	12	15,0	5,0	2
P0400.060-040-BR	M 6	40	24	12	15,0	5,0	2
P0400.080-012-BR	M 8	12	30	16	18,0	6,0	2
P0400.080-016-BR	M 8	16	30	16	18,0	6,0	2
P0400.080-020-BR	M 8	20	30	16	18,0	6,0	2
P0400.080-025-BR	M 8	25	30	16	18,0	6,0	2
P0400.080-030-BR	M 8	30	30	16	18,0	6,0	2
P0400.080-040-BR	M 8	40	30	16	18,0	6,0	2