



P0308

Material

Steel, zinc-plated (class 8), and stainless steel (A2 and A4).

Technical Notes

To DIN 980 V.

Reusable, resistant to shocks, vibrations and dynamic loads.

The locking function is achieved by the deformation of part of the nut. The nut will run smoothly until it reaches the deformed part at which point the clamping force will increase.

Order No.	d	h	A/F	Material
P0308.050-ZP	M 5	5	8	Steel ZP
P0308.060-ZP	M 6	6	10	Steel ZP
P0308.080-ZP	M 8	8	13	Steel ZP
P0308.100-ZP	M10	10	17	Steel ZP
P0308.120-ZP	M12	12	19	Steel ZP
P0308.140-ZP	M14	14	22	Steel ZP
P0308.160-ZP	M16	16	24	Steel ZP
P0308.200-ZP	M20	20	30	Steel ZP
P0308.240-ZP	M24	24	36	Steel ZP
P0308.300-ZP	M30	30	46	Steel ZP
P0308.030-A2	M 3	3	5,5	A2 s/s
P0308.040-A2	M 4	4	10	A2 s/s
P0308.050-A2	M 5	5	8	A2 s/s
P0308.060-A2	M 6	6	10	A2 s/s
P0308.080-A2	M 8	8	13	A2 s/s
P0308.100-A2	M10	10	17	A2 s/s
P0308.120-A2	M12	12	19	A2 s/s

Order No.	d	h	A/F	Material
P0308.160-A2	M16	16	24	A2 s/s
P0308.200-A2	M20	20	30	A2 s/s
P0308.220-A2	M22	22	32	A2 s/s
P0308.240-A2	M24	24	36	A2 s/s
P0308.030-A4	M 3	3	5,5	A4 s/s
P0308.040-A4	M 4	4	10	A4 s/s
P0308.050-A4	M 5	5	8	A4 s/s
P0308.060-A4	M 6	6	10	A4 s/s
P0308.080-A4	M 8	8	13	A4 s/s
P0308.100-A4	M10	10	17	A4 s/s
P0308.120-A4	M12	12	19	A4 s/s
P0308.160-A4	M16	16	24	A4 s/s
P0308.200-A4	M20	20	30	A4 s/s
P0308.220-A4	M22	22	32	A4 s/s
P0308.240-A4	M24	24	36	A4 s/s