



P2105

ANTI-VIBRATION COMPONENTS

Material

Rubber on yellow zinc plated steel (rubber hardness 45-65 Shore A).

for machines that move in three directions. Oil anti-drip hoods can be supplied on request.

air conditioners, ventilators and vibrating tables.

Technical Notes

The design of the mount makes them ideal

Tips

These mounts are found on compressors,

Order No.	Type	d ₁	d ₂	d ₃	h ₁	h ₂	l ₁	l ₂	Load kgf max.	Weight g
P2105.045-45	Type 1	33.0	M 8	8.0	25	2.0	66	85	20	70
P2105.045-60	Type 1	33.0	M 8	8.0	25	2.0	66	85	50	70
P2105.065-45	Type 1	52.0	M10	10.5	35	2.5	92	114	40	170
P2105.065-60	Type 1	66	M10	10.5	35	2.5	92	114	75	170
P2105.085-45	Type 1	52.0	M10	11.5	40	3.0	110	136	75	303
P2105.085-60	Type 1	52.0	M10	11.5	40	3.0	110	136	120	303
P2105.090-45	Type 1	57.5	M10	12.5	45	3.0	125	150	130	430
P2105.090-60	Type 1	57.5	M10	12.5	45	3.0	125	150	220	430
P2105.130-45	Type 2	78.0	M12	14.5	63	5.0	120	150	280	1080
P2105.130-60	Type 2	78.0	M12	14.5	63	5.0	120	150	500	1080
P2105.170-45	Type 2	100	M16	14.5	84	4.0	160	200	380	2390
P2105.170-60	Type 2	100	M16	14.5	84	4.0	160	200	750	2390
P2105.250-45	Type 2	187	M24	18.5	158	6.0	250	310	1400	10400
P2105.250-60	Type 2	187	M24	18.5	158	6.0	250	310	2500	10400



Recommendations for machine mounts

Machine mounts should be installed between two parallel and perfectly flat surfaces. Mounts operating tilted or twisted do not work properly. This may be due to incorrect alignment, tolerances in the building of the structure or over-tightened torque during the installation of the anti-vibration mounts.

