





# Gear Drive Chains

3,325 circular pitch

# Chains, Belts & Pulleys



**R1010**

CHAINS, BELTS & PULLEYS

**Material**

0,8mm Ø, stainless steel cable, encased in polyurethane (red).

Fibre cable core (aramid) also available (particularly suitable for reverse bend applications).

When ordering aramide core type add suffix -EF to order no.

**Technical Notes**

Infinite lengths, zero backlash, no lubrica-

tion, mass 13 grams/metre, positive drive, silent drive, extra strong 90A Durometer, Ultimate tensile strength 440N (40N/pin) when belt is used in open loop configuration (without splice, no crimp bushing). Temperature range +80°C to -25°C, Recommended operating load 108N, Recommended max. operating speed 1,91m/s.

Other no's of pitches available on request.

**Tips**


Self splice kit available (order no. R1010.SSK).

Reduce operating load rating by 50% for self splices.

**Important Notes**

Operates with R1011, R1012 series sprockets.

Order No.	No. of pitches	Length ref.
R1010.050	50	166.3
R1010.052	52	172.9
R1010.054	54	179.6
R1010.056	56	186.2
R1010.058	58	192.9
R1010.060	60	199.5
R1010.062	62	206.2
R1010.064	64	212.8
R1010.066	66	219.5
R1010.068	68	226.1
R1010.070	70	232.8
R1010.075	75	249.4
R1010.080	80	266.0
R1010.085	85	282.6
R1010.090	90	299.3
R1010.095	95	315.9
R1010.100	100	332.5
R1010.105	105	349.1
R1010.110	110	365.8
R1010.115	115	382.4
R1010.120	120	399.0
R1010.130	130	432.3
R1010.140	140	465.5
R1010.150	150	498.8
R1010.160	160	532.0
R1010.170	170	565.3
R1010.180	180	598.5



Order No.	No. of pitches	Length ref.
R1010.190	190	631.8
R1010.200	200	335.0
R1010.220	220	731.5
R1010.240	240	798.0
R1010.260	260	864.5
R1010.280	280	931.0
R1010.300	300	997.5
R1010.320	320	1064.0
R1010.380	380	1263.5
R1010.420	420	1396.5
R1010-1.5M	-	1,5 metres not spliced
R1010-3.0M	-	3,0 metres not spliced
R1010-7.5M	-	7,5 metres not spliced
R1010-15M	-	15,0 metres not spliced
R1010-30M	-	30,0 metres not spliced